

**Declaration of Performance  
No. 01125-00139-GB**

1. Unique identification code of the product-type:

**Panic exit devices according to DIN EN 1125:2008**

2. Product or product family as required pursuant to Article 11 (4), Regulation (EU) No 305/2011:

**Schloss GBS 143 in Verbindung mit Touch Bar EPN 2000 II**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**For doors in escape routes, even if these are fire resistance or smoke control doors and in conjunction with a door closer device.**

4. Name and contact of the manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:

**ECO Schulte GmbH & Co. KG  
Iserlohner Landstraße 89  
58706 Menden / Germany**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V, Regulation (EU) No 305/2011:

**System 1**

6. Das MPA NRW mit der Akkreditierungsnummer Nr. 0432 hat gemäß den Vorgaben der DIN EN 1125:2008 die Typprüfung vorgenommen und die Leistungsbeständigkeit nach System 1 bewertet und überprüft sowie das Zertifikat der Leistungsbeständigkeit 0432-CPR-00099-02 ausgestellt.

## 7. Declared performance:

**Harmonisierte technische Spezifikation: DIN EN 1125:2008**

| Essential characteristics        | Performance                                                                                                                                                                                                                                                                       |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Classification</b>            |                                                                                                                                                                                                                                                                                   |
| 7.1 Category of use              | Grade 3: High frequency of use                                                                                                                                                                                                                                                    |
| 7.2 Durability                   | Grade 7: 200.000 cycles                                                                                                                                                                                                                                                           |
| 7.3 Test door mass               | Grade 7: up to 300 kg                                                                                                                                                                                                                                                             |
| 7.4 Suitability fire/smoke doors | Grade B: Suitable                                                                                                                                                                                                                                                                 |
| 7.5 Safety                       | Grade 1: Suitable                                                                                                                                                                                                                                                                 |
| 7.6 Corrosion resistance         | Grade 3: 96 h [according to EN 1670]                                                                                                                                                                                                                                              |
| 7.7 Security                     | Grade 2: Suitable                                                                                                                                                                                                                                                                 |
| 7.8 Projection of device         | Grade 2: Standard projection                                                                                                                                                                                                                                                      |
| 7.9 Type of device               | Type B: Touch Bar operation                                                                                                                                                                                                                                                       |
| 7.10 Field of door application   | Grade A: Outside opening double escape door: active leaf                                                                                                                                                                                                                          |
| Type of panic function           | Function IV [B]<br>Split spindle hub, constantly active escape door function. It is always possible to use the handle in escape direction to open the door. The handle against escape direction is either permanently engaged or permanently released by turning the key. Against |

**Control of hazardous substances**

The materials used in this product contains no hazardous materials. Also, they give no more into the environment free , as allowed in any European standard or regulation.

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Tobias Schulte, Managing director ECO Schulte GmbH & Co. KG

(Signatory Name and function in company)

Menden, 01/16/2017

