

**Declaration of Performance  
No. 12209-00017-GB**

1. Unique identification code of the product-type:

**Mechanically operated locks according to DIN EN 12209:2003**

2. Product or product family as required pursuant to Article 11 (4), Regulation (EU) No 305/2011:

**ECO 127**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**The mortise lock ensures a proper closure of the door, even in conjunction with a door closer device or if it is a fire resistance or smoke control door**

4. Name and contact of the manufacturer as required pursuant to Article 11 (5), Regulation (EU) No 305/2011:

**ECO Schulte GmbH & Co. KG  
Iserlohner Landstraße 89  
58706 Menden / Germany**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V, Regulation (EU) No 305/2011:

**System 1**

6. Das MPA NRW mit der Akkreditierungsnummer Nr. 0432 hat gemäß den Vorgaben der DIN EN 12209:2003 die Typprüfung vorgenommen und die Leistungsbeständigkeit nach System 1 bewertet und überprüft sowie das Zertifikat der Leistungsbeständigkeit 0432-CPR-00099-03 ausgestellt.

7. Declared performance:

**Harmonisierte technische Spezifikation: DIN EN 12209:2003**

| Essential characteristics               | Performance                                       |
|-----------------------------------------|---------------------------------------------------|
| <b>Classification</b>                   |                                                   |
| 4.2.1 Category of use                   | Grade 3: Severe duty                              |
| 4.2.2 Durability                        | Grade M: 200.000 cycles, 25 N load on latch bolt  |
| 4.2.3 Door mass and closing force       | Grade 6: up to 300 kg and 25 N max. closing force |
| 4.2.4 Suitability fire/smoke doors      | Grade 1: Suitable                                 |
| 4.2.5 Safety                            | NPD (No Performance Determined)                   |
| 4.2.6 Corrosion resistance              | Grade D: 240 h [according to EN 1670]             |
| 4.2.7 Security and drill resistance     | Grade 3: Medium security and no drill resistance  |
| 4.2.8 Field of door application         | Grade B: Mortise lock for hinged door             |
| 4.2.9 Type of key operation and locking | Grade A: Cylinder lock; manually locking          |
| 4.2.10 Type of spindle operation        | Grade 2: Lock for unsprung lever handle operation |
| 4.2.11 Key identification requirement   | NPD (No Performance Determined)                   |

**Control of hazardous substances**

The materials used in this product contains no hazardous materials. Also, they give no more into the environment free , as allowed in any European standard or regulation.

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Tobias Schulte, Managing director ECO Schulte GmbH & Co. KG

(Signatory Name and function in company)

Menden, 06/19/2015

